

Central Office:

Unit 8, No 174, Jalal Al Ahmad Blu, Ashrafi Esfahani St, Tehran, Iran.

Phone: +98 21 44 27 3600 Whatsup: +98 910 929 17 90







Operation

Adjustable manual passage to either direction. Optional: Motorized

RVH 1100

Chassis

1.5 mm thick, AISI 304 quality stainless steel.
Optional: AISI 316 quality. With various color options electrostatic powder coated.

Rotor and Arms

3 wings, 10 arms. AISI 304 quality stainless steel.
Optional: AISI 316 quality. With various color options electrostatic powder coated.

Passage information. Ability to set the passage time. Memory mode. Adjustable audio warning. Remote controlled passage direction and enable feature.

Mechanism

Tempered steel and zinc coating.

Fail-Safe (Free passage during power failure). Optional: Fail lock.

Emergency Mode

The arms allow free passage when the signal received from fire detection system.

Operating Voltage 100-230 VAC, 47-60 Hz

Power Consumption

7W during passages, 12W during stand-by
Operating Temperature

-20° / +70° Optional: with heater -50°

Passage Speed

~20 persons / minute.

Passage Width

Weight

~215 kg

Security Level

High Security.

Indicators

Standart in both directions. Areas of Use

Suitable for indoor and outdoor use.

Accessories Heater. Internal lightening. Stainless steel reader bracket. Button control unit. Remote control unit. Coin console. Stainless steel bottom plate.

RS232 / RS485 / LAN communication unit. Adaptor.











