



RVH 2000 FULL HEIGHT TURNSTILE

Operation

Adjustable manual passage to either direction. Optional: Motorized

Chassis

1.5 mm thick, AISI 304 quality stainless steel.
Optional: AISI 316 quality. With various color options electrostatic powder coated.

Rotor and Arms

AISI 304 quality stainless steel.
Two single-arm rotors and 10 pieces of stainless steel arms.

Functions

Auto shut-off. Ability to set the passage time. Adjustable audio warning.

Mechanism

Tempered steel and zinc coating.
Fail-Safe (Free passage during power failure).

Emergency Mode

In case of emergency, manual button or signal from fire alarm system switches to emergency mode and wings automatically open in the direction previously set.

Operating Voltage

100-230 VAC, 47-60 Hz

Power Consumption

150W during passages, 18W during stand-by

Operating Temperature

-20° / +70° Optional: with heater -50°

Passage Speed

~8 persons / minute.

Passage Width

129 cm

Weight

~245 kg

Security Level

High Security.

Indicators

Standart in both directions.

Areas of Use

Suitable for indoor and outdoor use.

Accessories

Heater. Internal lightning. Stainless steel reader bracket. Button control unit.
Remote control unit. Stainless steel bottom plate.
RS232 / RS485 / LAN communication unit.

