



## RVH 1100 FULL HEIGHT TURNSTILE

### Operation

Adjustable manual passage to either direction. Optional: Motorized

### Chassis

1.5 mm thick, AISI 304 quality stainless steel.  
Optional: AISI 316 quality. With various color options electrostatic powder coated.

### Rotor and Arms

3 wings, 10 arms. AISI 304 quality stainless steel.  
Optional: AISI 316 quality. With various color options electrostatic powder coated.

### Functions

Passage information. Ability to set the passage time. Memory mode. Adjustable audio warning. Remote controlled passage direction and enable feature.

### Mechanism

Tempered steel and zinc coating.  
Fail-Safe (Free passage during power failure). Optional: Fail lock.

### Emergency Mode

The arms allow free passage when the signal received from fire detection system.

### Operating Voltage

100-230 VAC, 47-60 Hz

### Power Consumption

7W during passages, 12W during stand-by

### Operating Temperature

-20° / +70° Optional: with heater -50°

### Passage Speed

~20 persons / minute.

### Passage Width

56 cm

### Weight

~215 kg

### Security Level

High Security.

### Indicators

Standart in both directions.

### Areas of Use

Suitable for indoor and outdoor use.

### Accessories

Heater. Internal lightening. Stainless steel reader bracket. Button control unit.  
Remote control unit. Coin console. Stainless steel bottom plate.  
RS232 / RS485 / LAN communication unit. Adaptor.

