



## TRE 100D TRIPOD TURNSTILE

### Operation

Adjustable manual passage to either direction.

### Frame

Two-legged, flat covered, AISI 304 quality stainless steel. Optional: AISI 316 quality.

### Core and Arms

CNC-machined, aluminum cast core and polished. Ø40x2.5 mm aluminum arms  
Optional: Stainless steel arms.

### Functions

Passage information (NC: Normally close or NO: Normally open).  
Passage time. Memory mode. Audio warning. Adjustable passage direction.

### Mechanism

AISI 304 quality stainless steel. Fail-Safe (arms rotate freely during power failure)  
Optional: Fail Lock.

### Emergency Mode

The arms rotate freely with the signal received from fire detection system.  
Optional: Drop arm.

### Indicator

Direction LEDs for both directions. Optional: Upper lid.

### Operating Voltage

100-230 VAC. 47-60 Hz

### Power Consumption

7.6W during passage, 8.2W during standby

### Operating Temperature

-10° / +70° Optional: With heater -40°

### Passage Speed

~50 persons / minute.

### Passage Width

45-50 cm

### Weight

~52 kg

### Security Level

Deterrent.

### Areas of Use

Suitable for indoor and outdoor use.

### Accessories

Outdoor Cover. Unauthorized Passage Notification System. Meter. Button Control Unit. Remote Control Unit. Stainless Steel Bottom Plate. Plexiglass Reader Assembly Kit. Reader Assembly Apparatus. RS232 Communication Unit.

